

PRODUCT INFORMATION

## **M2000** PRO Q 1 **Tester Kit** MAX 25kN / 5620lbf

The M2000 tester

enables engineers to confirm the installation process has been carried out in accordance with the anchor manufacturers instructions.

The M2000 PRO Kit comprises all the necessary accessories to enable it to cover a pull test on a comprehensive range of fixings up to a maximum tensile load of 25kN.

The M2000 is compatible with the Hydrajaws Digital Reporting System\*

Record your test results digitally, manage your test schedule and generate reports online













## M2000 PRO Tester Kit

Manufactured to exacting high standards, the Hydrajaws M2000 PRO Tester Kit contains a universal set of adaptors allowing a wide range of anchors and fixings used in safety critical applications to be tested, up to a maximum tensile load of 25kN.

The three-legged load spreading bridge keeps reaction loads away from the fixing allowing results to be more consistent.

Trusted by market leading companies worldwide, the M2000 PRO Tester Kit is an essential tool for

carrying out testing procedures in line with BS 8539 and BS 7883.

The M2000 PRO Tester Kit is easy to use and easily transported. It comes complete with a comprehensive full colour user manual and the backing and support from our technical team at Hydrajaws.

Supplied with a 12-month calibration certificate, the gauge is detachable enabling it to be returned to Hydrajaws for recalibration ensuring its accurate performance for years to come.

## M2000 Pro Kit Features





- 0-25kN Dual Scale digital gauge (detachable for calibration, reduces carrier return costs)
- 2020 Load spreading bridge featuring height adjustable legs with pin arrangement in four positions with swivel feet giving 15mm of fine adjustment
- Turning Handle with 22mm (7/8") integrated nut (for use in confined spaces)
- Hydrajaws gauge calibration certificate (valid for 12 months)
- The tester is preassembled and accessories can be quickly changed with ease
- Each kit comes in a robust carry case

Kit includes the following adaptors:

- M12 Ringbolt Adaptor Clevis
- Bolt tester adaptor with M12 locking adaptor
- M16 & M20 Threaded stud adaptors
- Six slotted button adaptors (mm): 4.5, 5.5, 6.5, 8.5, 10.5, 12.5
- Six threaded button adaptors: M4, M5, M6, M8, M10, M12

- **TECHNICAL DATA**
- Pull-out load range: 0-25kN (5620 lbf)
- Up to 50mm stroke (1.97")
- Weight: Tester only 2.2kg (4.85 lbs) Oil type:
- LSB dimensions between feet edge: 116mm (4.57")
- Case dimensions: 571 x 382 x 160mm (22.48 x 15.04 x 6.30")
- Case weight: 10kg
- ISO VG 32 Mineral Based Oil
- Oil Replenishment via supplied oil bottle with aid of piston key
- Warranty: 12 months
- Part #: 200-001 (Metric Analog) Part #: 200-002 (Metric Digital) Part #: 200-008 (Imperial Analog) Part #: 200-009 (Imperial Digital)





YDRAJAWS<sup>®</sup> 73 Kettlebrook Road | Tamworth | United Kingdom | B77 1AG T: +44 (0)1675 430 370 | E: tester@hydrajaws.co.uk | W: hydrajaws.co.uk

