



**THE DURAPAC AUTO TWO SPEED POWER UNIT RANGE OFFERS HIGH PERFORMANCE FLOW COMBINATIONS FOR APPLICATIONS REQUIRING SPEED AND POWER.**

Single phase 08 Series have a universal motor and are ideal for field use with generators. Single phase 1.5 kW versions operate on a standard 10 amp power source and provide high flows in a portable package. Three phase 3 and 4 kW, 415 Volt versions are ideal for operating medium to large tonnage cylinders and systems.

All power units have an externally adjustable pressure relief valve and offer a range of directional control valve options to operate single and double acting cylinders and tools. An optional sub-plate style pilot check valve is also available.

**4 WAY MANUAL VALVE**



4 Way/3 Position directional control valve for controlling double acting cylinders.

**3 WAY MANUAL VALVE**



3 Way/3 Position directional control valve for controlling single acting cylinders.

**3 & 4 WAY SOLENOID VALVE**



3 and 4 Way/3 Position directional control valve for remote actuation of cylinders.

Model No.	Flow Rate (Lpm)		Pressure Rating (bar)		Motor kW	Voltage (50 Hz)	Amps	Remote Pendant Function 4 mtr	Valve Type (3/8 NPTF Ports) Sol.= Solenoid Man.= Manual	Useable Oil Cap. (L)	Approx. Dry Weight (kg)	Approx Dimensions (mm)
	1st Stage	2nd Stage	1st Stage	2nd Stage								
<b>08 SERIES</b>												
PEM8414 <sup>^</sup>	10.5	0.9	50	700	0.84	240	10.0	MOTOR ON/OFF	4w/3p Man.	7	25	320 W x 400 L x 565 H
PEM8424 <sup>^</sup>	10.5	0.9	50	700	0.84	240	10.0	MOTOR ON/OFF	4w/3p Man.	20	41	368 W x 490 L x 715 H
<b>15 SERIES</b>												
PEM1513	9.5	1.1	65	700	1.5	240	8.3	MOTOR ON/OFF	3w/3p Man.	10	46	270 W x 410 L x 565 H
PEM1523	9.5	1.1	65	700	1.5	240	8.3		3w/3p Man.	20	53	300 W x 450 L x 605 H
PEM1514	10.5	0.9	65	700	1.5	240	8.3		4w/3p Man.	10	46	270 W x 410 L x 565 H
PEM1524	9.5	1.1	65	700	1.5	240	8.3		4w/3p Man.	20	53	300 W x 450 L x 605 H
PES1513	9.5	1.1	65	700	1.5	240	8.3	SOLENOID ADV/HOLD/RETRACT	3w/3p Sol.	10	51	270 W x 410 L x 565 H
PES1523	9.5	1.1	65	700	1.5	240	8.3		3w/3p Sol.	20	58	300 W x 450 L x 605 H
PES1514	9.5	1.1	65	700	1.5	240	8.3		4w/3p Sol.	10	51	270 W x 410 L x 565 H
PES1524	9.5	1.1	65	700	1.5	240	8.3		4w/3p Sol.	20	58	300 W x 450 L x 605 H
<b>30 SERIES</b>												
PEM3023	10.5	2.1	100	700	3.0	415	6.3	*	3w/3p Man.	20	71	320 W x 450 L x 560 H
PEM3043	10.5	2.1	100	700	3.0	415	6.3	*	3w/3p Man.	40	78	320 W x 460 L x 680 H
PEM3024	10.5	2.1	100	700	3.0	415	6.3	*	4w/3p Man.	20	71	320 W x 450 L x 560 H
PEM3044	10.5	2.1	100	700	3.0	415	6.3	*	4w/3p Man.	40	78	320 W x 460 L x 680 H
PES3023	10.5	2.1	100	700	3.0	415	6.3	SOLENOID ADV/HOLD/RETRACT	3w/3p Sol.	20	77	320 W x 450 L x 560 H
PES3043	10.5	2.1	100	700	3.0	415	6.3		3w/3p Sol.	40	84	320 W x 460 L x 680 H
PES3024	10.5	2.1	100	700	3.0	415	6.3		4w/3p Sol.	20	77	320 W x 450 L x 560 H
PES3044	10.5	2.1	100	700	3.0	415	6.3		4w/3p Sol.	40	84	320 W x 460 L x 680 H
<b>40 SERIES</b>												
PEM4023	14.0	3.0	110	700	4.0	415	8.85	*	3w/3p Man.	20	80	320 W x 450 L x 590 H
PEM4043	14.0	3.0	110	700	4.0	415	8.85	*	3w/3p Man.	40	87	320 W x 460 L x 710 H
PEM4024	14.0	3.0	110	700	4.0	415	8.85	*	4w/3p Man.	20	80	320 W x 450 L x 590 H
PEM4044	14.0	3.0	110	700	4.0	415	8.85	*	4w/3p Man.	40	87	320 W x 460 L x 710 H
PES4023	14.0	3.0	110	700	4.0	415	8.85	SOLENOID ADV/HOLD/RETRACT	3w/3p Sol.	20	86	320 W x 450 L x 590 H
PES4043	14.0	3.0	110	700	4.0	415	8.85		3w/3p Sol.	40	93	320 W x 460 L x 710 H
PES4024	14.0	3.0	110	700	4.0	415	8.85		4w/3p Sol.	20	86	320 W x 450 L x 590 H
PES4044	14.0	3.0	110	700	4.0	415	8.85		4w/3p Sol.	40	93	320 W x 460 L x 710 H

\* Standard supply is motor mounted ON/OFF/JOG switch. Remote pendant is optional. To order with remote pendant, place suffix "R" behind pump model number. ^ Standard supply includes roll frame and 63mm diameter pressure gauge.