

"Makin' the Hard Jobs Easy"

CHAINSAWS



STANLEY DS06

The DS06 is lightweight, powerful and ideal for fast cutting of concrete, reinforced concrete, conduit, brick, stone and other masonry. 13 inch plunge cut capability allows quick cutting of window, door, conduit and duct openings in walls and notching and trimming of concrete pipe. Trigger activated water for lubrication and cooliong is ported through the bar and applied at the point where the concrete is being cut.

The DS06 is provided with The Wall Walker[™] to provide leverage for cutting, watter connection, and flush face quick disconnect couplers. The bar and chain are sold separately.

Specifications

Application: Cutting concrete, reinforced concrete, conduit, brick, stone

and other masonry.

Capacity: 13 in. / 33 cm Bar

Hyd. Flow: 4-6 or 7-9 gpm / 15-23 or 26-34 lpm

(see ordering info) **Weight:** 14 lbs / 6 kg **Length:** 24 in. / 61 cm **Width:** 9 in. / 23 cm

Connection: 3/8 in. flush face quick disconnect couplers

Model	Part No.	Weight	Length	Width	Flow Range	Working Pressure	Full Relief Setting	Output	Discharge
						1000-2000 psi / 70-140 bar			
DS06						1000-2000 psi / 70-140 bar			
	DS06300001*	14 lbs / 6 kg	24 in. / 61 cm	9 in. / 23 cm	7-9 gpm / 26-34 lpm	1000-2000 psi / 70-140 bar	2250 psi / 155 bar	13 in. / 33 cm Bar	CE

Model	Part No.	Description
	35037	Bar, 13 in. Sprocket Nose
DS06	56799	Diamond Chain, 13 in. Ultra 25
	56800	Diamond Chain, 13 in. Pinnacle 25
	65797	Flap Kit
DS06/	20857	Chain Repair Spinner
DS11	20858	Chain Repair Spinner
	20859	Diamond Chain Butterfly Repair Kit
	26020	Water Pump Kit, 115/230 Volt, 60 hz
	29361	HP1 Vanguard engine Water Pump Kit
	60859	Water Flow Meter, 0-7 gpm
	56767	Connecting Link, 5-Pack





"Makin' the Hard Jobs Easy"

CHAINSAWS

STANLEY DS11

The DS11 is lightweight, powerful and ideal for fast cutting of concrete, reinforced concrete, conduit, brick, stone and other masonry. Plunge cut capability allows quick cutting of window, door, conduit and duct openings in walls and notching and trimming of concrete pipe. Trigger activated water for lubrication and cooliong is ported through the bar and applied at the point where the concrete is being cut.

The DS11 features ergonomic handles and guards to help reduce operator fatigue, water connection, flush face quick disconnect couplers, and is powered by a Stanley Hyrevz[™] motor. The Wall Walker[™] that provides leverage for cutting is standard equipment. The bar and chain are sold separately.

Specifications

Application: Cutting concrete, reinforced concrete, conduit, brick, stone

and other masonry.

Capacity: 15 or 18 in. / 33 or 46 cm Bar

Hyd. Flow: 7-9 gpm / 26-34 lpm

(see ordering info) **Weight:** 26 lbs / 11 kg **Length:** 38 in. / 97 cm **Width:** 9 in. / 23 cm

Connection: 3/8 in. flush face quick disconnect couplers



Model	Part No.	Weight	Length	Width	Flow Range	Working Pressure	Full Relief Setting	Output	Discharge
DS11	DS113000*	26 lbs / 11 kg	38 in. / 97 cm	9 in. / 23 cm	7-9 gpm / 26-34 lpm	1000-2000 psi / 70-140 bar	2250 psi / 155 bar	15, 18 in. / 33 46 cm Bar	-

Model	Part No.	Description
	28232	Tool Box
	30305	Bar, 15 in., sprocket nose
	30306	Bar, 18 in., sprocket nose
	39496	SpeedHook® Kit
	39497	42 in. SpeedHook® Rail
DS11	39501	Saw mounting bracket assy
	56801	Diamond Chain, 15 in., Ultra 32
	56802	Diamond Chain, 18 in., Ultra 37
	56803	Diamond Chain, 15 in., Pinnacle 32
	58632	Diamond Chain, 18 in., Pinnacle 37
	23517	Sprocket Wrench

