



"Makin' the Hard Jobs Easy"

DBD-16L

DIAMOND

DBD-25X 25 86



DBD-25L 25 61



Both the DBD-25X and the smaller, lighter DBD-25L are prized field models because of their proven durability and ability to bend 25mm (1") 450N/mm² tensile strength rebars. For rebars of up to 20mm (3/4"), the DBD-19L is similarly treasured. Optional foot control, stand and bender covers are available for all three models.



DBD-19L 20 40



SPECIFICATIONS

Model	DBD-25H	DBD-25X	DBD-25L	DBD-19L	DBD-16L
Max.rebar diameter		25mm (1")		20mm (3/4")	16mm (5/8")
Bending speed	9 sec.	6 sec /180°	7 sec /180°	5 sec /180°	1.5 sec /180°
Max.tensile strength	820N/mm ²	560N/mm ²		490N/mm ²	
Bending angle	Up to 180°				
Power supply	Single phase mains electricity / Generator				
Voltage	100V/115V/230V				
Power input	1500W	1330W	1700W	1050W	
Weight	97 kg	86 kg	61 kg	40.8 kg	20 kg
Dimensions (mm)	540×580×440	490×550×440	462×320×415	320×425×415	320×350×245

Optional attachments: stand, footswitch

DBD-16L 16 20

This small unit may be carried in one hand but has all the attributes of its bigger brethren and can make a 180° bend in a 16mm (5/8") rebar in just 1.5 seconds.

