



*"Makin' the Hard Jobs Easy"*

# DBD-19L

**DIAMOND**

**DBD-25X** 25 86



**DBD-25L** 25 61



Both the DBD-25X and the smaller, lighter DBD-25L are prized field models because of their proven durability and ability to bend 25mm (1") 450N/mm<sup>2</sup> tensile strength rebars. For rebars of up to 20mm (3/4"), the DBD-19L is similarly treasured. Optional foot control, stand and bender covers are available for all three models.

**DBD-19L** 20 40



## SPECIFICATIONS

Model	DBD-25H	DBD-25X	DBD-25L	DBD-19L	DBD-16L
Max.rebar diameter		25mm (1")		20mm (3/4")	16mm (5/8")
Bending speed	9 sec.	6 sec /180°	7 sec /180°	5 sec /180°	1.5 sec /180°
Max.tensile strength	820N/mm <sup>2</sup>	560N/mm <sup>2</sup>		490N/mm <sup>2</sup>	
Bending angle	Up to 180°				
Power supply	Single phase mains electricity / Generator				
Voltage	100V/115V/230V				
Power Input	1500W	1330W	1700W	1050W	
Weight	97 kg	86 kg	61 kg	40.8 kg	20 kg
Dimensions (mm)	540×580×440	490×550×440	462×320×415	320×425×415	320×350×245

Optional attachments: stand, footswitch

**DBD-16L** 16 20

This small unit may be carried in one hand but has all the attributes of its bigger brethren and can make a 180° bend in a 16mm (5/8") rebar in just 1.5 seconds.

