



"Makin' the Hard Jobs Easy"

HAMMER DRILLS

MODEL HD08

The HD08 is ideal for just about any drilling job whether in rock, concrete, wood, or masonry. With 4500 blows per minute and 1175 rpm the powerful hammer function makes it easy to drill in rock, concrete, masonry and other such materials. The hammer function can be turned off for efficient light drilling in wood and metal. The HD08 features an integral gear motor, built-in flow control, depth gauge, assist handle, and dual-spool capability for operation on open-center or closed-center hydraulic systems. Optional bit holders are available for rope thread bits, twist groove shank bits, and taper shank bits.



Specifications

Application: Drilling in rock, concrete, wood or masonry.

Capacity: SDS Plus Drill Bits - up to 7/8 inches in concrete

Hyd. Flow: 3-9 gpm / 11-34 lpm

Weight: 6 lbs. / 2.7 kg

Length: 13 in. / 35 cm

Width: 5.5 in. / 14 cm

Connection: 3/8 NPT Male Pipe to -8 SAE port
(couplers sold separately)

Hammer Drills

Model	Part No.	Weight	Length	Width	Flow Range	Working Pressure	Full Relief Setting	Performance	Capacity	Misc.
HD08	HD08531G	6 lbs / 2.7 kg	13 in. / 35 cm	5-1/2 in / 14 cm	3-9 gpm / 11-34 lpm	750-2000 psi / 50-140 bar	2250 psi / 155 bar	1175 rpm @ 6 gpm	7/8 in. Dia	SDS Plus Shk
	HD0853101	6 lbs / 2.7 kg	13 in. / 35 cm	5-1/2 in / 14 cm	3-9 gpm / 11-34 lpm	750-2000 psi / 50-140 bar	2250 psi / 155 bar	1175 rpm @ 6 gpm	7/8 in. Dia	SDS Plus Shk; CE

Hammer Drill Accessories

Model	Part No.	Description
HD08	16769	1/2 in. Geared Chuck
	16770	Chuck Adapter 3/4 in. x 24 in.

Carbide Bits

Model	Part No.	Description
HD08	27807	3/8 x 12 in. OAL
	27814	1/2 x 2 in. OAL
	27826	3/4 x 12 in. OAL
	27827	3/4 x 18 in. OAL
	27832	7/8 x 18 in. OAL

STANLEY





"Makin' the Hard Jobs Easy"

HAMMER DRILLS

MODEL HD45

The HD45 is designed for drilling holes in concrete, rock or masonry from 3/4 in. / 19 mm to 2 in. / 50 mm in diameter and up to 29 in. / 73.7 cm deep as well as core drilling up to 4 in. / 102 mm in diameter. The HD45 uses a Skil 736 shank, carbide tipped, fluted drill bits and requires no fluid or compressed air to clear holes during operation. The HD45 features a feathering trigger for easy starts, adjustable rotation speed (both forward and revers), and is furnished with hose whips and flush face quick disconnect couplers.

Specifications

Application: Drilling holes in concrete, rock, or masonry.
Capacity: #736 Skil Hex
Hyd. Flow: 7-9 gpm / 26-34 lpm
Weight: 45 lbs. / 20 kg
Length: 22 in. / 57 cm
Width: 14 in. / 35 cm
Connection: 3/8 in. flush face quick disconnect couplers



Hammer Drills

Model	Part No.	Weight	Length	Width	Flow Range	Working Pressure	Full Relief Setting	Performance	Capacity	Misc.
HD45	HD45110B	45 lbs / 20 kg	22 in. / 57 cm	14 in / 35 cm	7-9 gpm / 26-34 lpm	1500-2000 psi / 50-140 bar	2250 psi / 155 bar	300 rpm	#736 Skil Hex	-
	HD451101	45 lbs / 20 kg	22 in. / 57 cm	14 in / 35 cm	7-9 gpm / 26-34 lpm	1500-2000 psi / 50-140 bar	2250 psi / 155 bar	300 rpm	#736 Skil Hex	CE

Hammer Drill Accessories

Model	Part No.	Description
HD45	27902	Percussion Core Bit 2-1/2 in. dia. x 6 in. OAL
	27904	Percussion Core Bit 3 in. dia. x 6 in. OAL
	30279	HD45 (Skill 736) Adapter (required)

Carbide Bits

Model	Part No.	Description
HD45	02280	3/4 x 24 in.
	02281	1 x 24 in.
	02282	1-1/4 x 24 in.
	02283	2 x 24 in.
	04668	1 x 18 in.
	04896	1-1/4 x 36 in.
	05163	7/8 x 24 in.
	05167	1-1/2 x 24 in.

STANLEY

