



"Makin' the Hard Jobs Easy"

## IZUMI P-132

MODEL No.  
**P-132**

Cuts insulated cables up to 132 mm



P-132



P-132 shown with P-60



### SPECIFICATIONS

Maximum input pressure :  
68.5 Mpa (10,000 PSI)  
Oil volume required : 220 cc

Output force : 95 kN

### SIZE

630 (L) mm

### WEIGHT

12.0 kg

### ACCESSORIES

Carrying bag

### FEATURES

P-132 hydraulic cutter head features :

- \* Cuts underground or armored cables (depends on type)
- \* Fast cutting with remote operation
- \* Guillotine type cutting for less jamming than shear type cutting
- \* 132mm jaw opening accepts larger size cables
- \* Can be operated by any hydraulic pump with rated oil pressure of 68.5 Mpa (10,000 PSI)
- \* Equipped with NPT 3/8" threaded Parker type high pressure couplers
- \* Blades are easily replaceable
- \* Lock pin type cutter head

### REMARKS

Cutting of piano wire is prohibited.

Cutting capacity

Cu strands : 42 mm  
Al strands : 46 mm

Wire rope 6x7 : N/A  
Wire rope 6x12 : N/A  
Wire rope 6x19 : N/A  
Soft steel bar : N/A  
Reinforcing rod : N/A  
ACSR : N/A  
Guy wire 1x7 : N/A  
Guy wire 1x19 : N/A

\*Quality backed by ISO 9001