



"Makin' the Hard Jobs Easy"

IZUMI S-240

MODEL No.
S-240

Cuts steel materials as well as cables up to 24 mm



S-240



S-240 (Latch opened)

SPECIFICATIONS

Maximum handle load : 226 N
Two stage pumping
Relief valve is not equipped
Reservoir capacity : 120 cc
Maximum opening : 24 mm
Pumping cycles when no load :
13 times

Output force : 84 kN

SIZE

475 (L) mm

WEIGHT

4.9 kg

ACCESSORIES

Carrying bag

FEATURES

Light weight portable hydraulic cutter features :

- * Two stage pumping for rapid blade advance
- * Guillotine type cutting for less jamming than shear type cutting
- * No set-up time required
- * Blades are easily replaceable
- * 180 degree swivel and latch type head allows easy cutting position

REMARKS

Cutting of piano wire is prohibited.

Cutting capacity

Wire rope 6 x 7	: 18 mm
Wire rope 6 x 12	: 24 mm
Wire rope 6 x 19	: 24 mm
Soft steel bar	: 20 mm
Reinforcing rod	: 16 mm
Cu strands	: 24 mm
Al strands	: 24 mm
ACSR	: 24 mm
Guy wire 1 x 7	: 20 mm
Guy wire 1 x 19	: 20 mm
CCP cable	: N/A