



"Makin' the Hard Jobs Easy"

# IZUMI S-550G

MODEL No.  
**S-550G**

Cuts steel materials as well as cables up to 54 mm



S-550G



## SPECIFICATIONS

Maximum handle load : 276 N  
Two stage pumping  
Relief valve is equipped  
Reservoir capacity : 202 cc  
Maximum opening : 56 mm  
Pumping cycles when no load :  
25 times

Output force : 124 kN

## SIZE

625 (L) mm

## WEIGHT

10.0 kg

## ACCESSORIES

Carrying bag

## FEATURES

The S-550G is designed to cut the toughest steel used in construction site.

Guillotine type cutting for less jamming than scissors type cutting.

This cutter is suitable for ACSR cable.

The head shear plate instead of one complete head unit as previous S-550 gives low replacement cost.

## REMARKS

Cutting of piano wire is prohibited.

Cutting capacity

Wire rope 6 x 7	: 25 mm
Wire rope 6 x 12	: 30 mm
Wire rope 6 x 19	: 30 mm
Soft steel bar	: 22 mm
Reinforcing rod	: 19 mm
Cu strands	: 54 mm
Al strands	: 54 mm
ACSR	: 54 mm
Guy wire 1 x 7	: 15 mm
Guy wire 1 x 19	: 20 mm
CCP cable	: N/A