



MODEL No.

Cuts heavy duty steel materials up to 32 mm



SPECIFICATIONS

Maximum input pressure : 68.5 Mpa Oil volume required : 135 cc

Output force : 250 kN

SIZE

300 (L) mm

WEIGHT

10.0 kg

ACCESSORIES

Carrying bag

3r-97



FEATURES

The SP-32 hydraulic cutter head features :

- * Fast cutting with remote operation
- * It can be operated by any hydraulic pump with rated oil pressure of 68.5 Mpa (10,000 PSI)
- * Equipped with PT 3/8" threaded Izumi high pressure couplers
- * PT-NPT adapters are available on request for NPT 3/8" threaded couplers
- * Blades are easily replaceable
- * Flip-top latch for easy insertion of cutting material

REMARKS

Cutting of piano wire is prohibited.

Cutting capacity

Wire rope 6 x 7	: 32 mm
Wire rope 6 x 12	: 32 mm
Wire rope 6 x 19	: 32 mm
Soft steel bar	: 25 mm
Reinforcing rod	: 25 mm
Cu strands	: 32 mm
AI strands	: 32 mm
ACSR	: 32 mm
Guy wire 1 x 7	: 32 mm
Guy wire 1 x 19	: 32 mm
CCP cable	: N/A

www.htc.co.nz

0800 48 2000