



"Makin' the Hard Jobs Easy"


IZUMI SP-55A

MODEL No.
SP-55A

Cuts steel materials as well as cables
up to 55 mm



SP-55A



SPECIFICATIONS

Maximum input pressure :
68.5 Mpa
Oil volume required : 120 cc

Output force : 118 kN

SIZE

415 (L) mm

WEIGHT

9.0 kg

ACCESSORIES

Carrying bag

FEATURES

The SP-55A hydraulic cutter head features :

- * Fast cutting with remote operation
- * It can be operated by any hydraulic pump with rated oil pressure of 68.5 Mpa (10,000 PSI)
- * Equipped with PT 3/8" threaded Izumi high pressure couplers
- * PT-NPT adapters are available on request for NPT 3/8" threaded couplers
- * Blades are easily replaceable
- * Lock pin type cutter head

REMARKS

Cutting of piano wire is prohibited.

Cutting capacity

Wire rope 6 x 7	: 25 mm
Wire rope 6 x 12	: 30 mm
Wire rope 6 x 19	: 30 mm
Soft steel bar	: 22 mm
Reinforcing rod	: 19 mm
Cu strands	: 50 mm
Al strands	: 50 mm
ACSR	: 50 mm
Guy wire 1 x 7	: 15 mm
Guy wire 1 x 19	: 20 mm
CCP cable	: N/A