

# COMPOSITLOCK POLES

HHH (JAMESON)

## **COMPOSITLOCK**<sup>™</sup>

## Jameson's Latest Innovation In Poles!

Developed in response to safety concerns from our customers, Jameson offers fiberglass COMPOSITLOCK<sup>™</sup> Poles with fiber reinforced composite ferrules.

COMPOSITLOCK<sup>™</sup> Poles maintain insulating properties across pole sections for line-clearance tree work PLUS offer more secure pole connection for telecommunication, line clearance, arborist and landscape professionals.

## **BENEFIT S**

## INCRE ASED SAFETY WHEN WORKING AROUND ENERGIZED LINES

R esponding in part to the TCIA EHAP<sup>®</sup> Program and NRECA Commitment to Zero Contacts initiative, Jameson's CompositLock<sup>™</sup> Fiberglass Poles seek to reduce the potential for conductivity.

## S TRONG, SECURE CONNECTIONS BETWEEN POLE SECTIONS

Over-sized thread profile provides strong, secure connections, eliminating loose fit or "slop" required with traditional aluminum ferrules. The result is less binding, easy cleaning, and improved rigidity the entire working length of the pole.

## SMO OTH FERRULE PROFILE

Sunk en rivets and threaded attachment result in a smooth profile that moves easily in foliage without snagging

Not A "Hot Stick" - Not For Use On Energized Lines





SALES • SERVICE • CALIBRATION • HIRE

0800 48 2000

## "Makin' the Hard Jobs Easy"

<u>COMPOSITLOCK POLES</u>

## JEC FOAM CORE COMPOSITLOCK<sup>™</sup> POLE

PREFERRED FOR AERIAL CONSTRUCTION & LINE CLEARANCE

Jameson's JE Series foam core pole is the highest quality fiberglass pole available.

- Foam core prevents debris and moisture build up inside pole and adds extra hoop strength and rigidity
- Polymer protective surface veil prevents fiber blooming at surface due to abrasion
  or ultra-violet light




 Meets requirements of OSHA Standard 1910.269(j)(1)(i): Individually tested to 100KV per foot for five minutes

| Pole Length | 4'       | 6'       | 8'       | 10'       | 12'       |
|-------------|----------|----------|----------|-----------|-----------|
| Base        | JEC-4F   | JEC-6F   | JEC-8F   | JEC-10F   | JEC-12F   |
| Extension   | JEC-4    | JEC-6    | JEC-8    | JEC-10    | JEC-12    |
| Saw Head    | JEC-4SFP | JEC-6SFP | JEC-8SFP | JEC-10SFP | JEC-12SFP |

## FGC HOLLOW CORE COMPOSITLOCK<sup>™</sup> POLE

PREFERRED FOR TREE TRIMMING & AERIAL CONSTRUCTION Jameson's strongest and most popular pole is lighter than foam core poles, offering greater control and exceptional bend strength. Batch tested per ASTM F711.<sup>++</sup>

• Polymer protective surface veil prevents fiber blooming at surface due to abrasion or ultra-violet light



| Pole Length | 4'       | 6'       | 8'       | 10'       | 12'       |
|-------------|----------|----------|----------|-----------|-----------|
| Base        | FGC-4F   | FGC-6F   | FGC-8F   | FGC-10F   | FGC-12F   |
| Extension   | FGC-4    | FGC-6    | FGC-8    | FGC-10    | FGC-12    |
| Saw Head    | FGC-4SFP | FGC-6SFP | FGC-8SFP | FGC-10SFP | FGC-12SFP |

## EXTENSION POLE

SAW HEAD POLE

mounted saw head for attaching saw

Female ferrule and permanently

blade.

Male and female ferrules to attach additional poles or tools. Provides additional length (workable height).



## BASE POLE

Rubber end cap and male ferrule to attach poles or tools. Provides solid foundation. Jameson recommends starting with Base Pole. **BLC HOLLOW CORE COMPOSITLOCK<sup>™</sup> POLE** 

### THE LIGHTWEIGHT OPTION FOR TREE TRIMMING

Jameson's highest strength-to-weight ratio pole is lightweight and easy to control, making it ideal for tree trimming. BL poles are batch tested per ASTM F711.<sup>++</sup>

- Durable enamel coating prevents fiber blooming at surface due to abrasion or ultra-violet light
- Batch tested to 100KV per foot for five minutes.

| Pole Length | 4'       | 6'       | 8'       | 10'       | 12'       |
|-------------|----------|----------|----------|-----------|-----------|
| Base        | BLC-4F   | BLC-6F   | BLC-8F   | BLC-10F   | BLC-12F   |
| Extension   | BLC-4    | BLC-6    | BLC-8    | BLC-10    | BLC-12    |
| Saw Head    | BLC-4SFP | BLC-6SFP | BLC-8SFP | BLC-10SFP | BLC-12SFP |



## www.htc.co.nz email: info@htc.co.nz

SALES • SERVICE • CALIBRATION • HIRE

0800 48 2000