



"Makin' the Hard Jobs Easy"

PCW5000

PCW5000

PRO SERIES

**Gas-Powered
Pulling Winch GXH50**



**SINGLE LINE
PULLING FORCE
2,200 LB**



**DOUBLE LINE
PULLING FORCE
4,400 LB**



**WINCH TILT
+/- 20°**



**SPEED
MAX 40' / MIN**



**WEIGHT
35 LB**



**POWER
1.6 kW | 2.1 HP**



**MOTORIZATION
HONDA 4-STROKE GXH50**



**POWERED BY
GAS**



**PRIVATE USE
WARRANTY
5 YEARS**



Series

Designed in

Motor/Engine

Powered by

Drive/Clutch

Rope Retention System

Drum turns when motor/engine is idling

Pulling Capacity

Standard drum (single line / double line)

Optional drum (single line / double line)

Lifting Capacity

Standard drum (single line / double line)

Optional drum (single line / double line)

Speed

Standard drum

Optional drum

Weight

Dimensions (overall)

Gearbox

Gear ratio

Brake

Rope (not included)

Length

Minimum diameter

Maximum diameter

Recommended diameter

Included

Warranty

Private use

Commercial use

Motor/Engine

Certification

PCW5000

Pro

2003

POWERED by

HONDA

Honda GXH50

4-stroke air-cooled

1.6 kW - 2.1 HP @ 7,000 tr/min

Gas

Direct drive (no clutch)

No

Yes

Ø 2-1/4" (57 mm) : 2,200 lb / 4,400 lb

Ø 3-3/8" (85 mm) : 1,600 lb / 3,200 lb

Not designed for lifting - See **INDUSTRIAL SERIES** winches

Ø 2-1/4" (57 mm) : 40'/min

Ø 3-3/8" (85 mm) : 60'/min

35 lb

14-5/8" x 14-3/8" x 14-3/8"

Aluminium alloy. Heat treated 3-stage spur gears.

Mounted on ball bearings. Oil bath lubrication.

110:1

Anti-reversing roller clutch bearing

Low stretch double braided polyester

Unlimited

Ø 3/8" (10 mm)

Ø 1/2" (13 mm)

Ø 1/2" (12 mm)

Round polyester sling - 8'

Get 1 additional year of warranty if you register your product at

www.portablewinch.com

5 years

1 year

Honda International Warranty

CE

www.htc.co.nz

email: info@htc.co.nz

SALES • SERVICE • CALIBRATION • HIRE

0800 48 2000