



"Makin' the Hard Jobs Easy"

# STANLEY CS06620



**CHAIN SAW**

**CS06620**



## SPECIFICATIONS

ITEM	U.S.A.	METRIC
Capacity	15 in.	38 cm
Weight *	6.25 lb	2.8 kg
Length*	14 in.	36 cm
Width	9 in.	23 cm
Pressure	1000-2000 psi	70-140 bar
Flow Range	7-9 gpm	26-34 lpm
Optimum Flow	8 gpm	30 lpm
Porting	-8 SAE O-Ring	
Connect Size and Type	3/8 in. NPT Male Adapter	
Hose Whips	No	
Motor	Integral	

\* Without Bar

### FEATURES AND BENEFITS

Stanley's CS06620 Hydraulic Chain Saw offers the highest power-to-weight ratio of any chain saw on the market today. It is ideal for bucket truck use because of its wide range of flow and pressure requirements.

It's used around the world by utility companies, professional tree trimmers and construction crews for all types of pruning and cleaning applications.

Safety features include interlocking triggers, hand guards and low kickback bars and chains. Hydraulic power doesn't require a flywheel to smooth power pulses so there is no chain coasting when the trigger is released.

Kickback is also reduced without the centrifugal force from the flywheel used on gas driven saws. The CS06620 features a floating rim sprocket for longer wear and easy replacement.

The CS06620 can be ordered in a variety of bar lengths and comes standard with a dual spool which provides the flexibility to use on either an open or closed-center hydraulic system.

The powerful CS06620 is designed for use on HTMA Type II circuits with a full 8 gpm/30 lpm output.



"Makin' the Hard Jobs Easy"

# STANLEY CS06620

## ORDERING INFORMATION

MODEL NO.	DESCRIPTION
CS06620	Chain Saw, OC/CC, 15 in. Cut, 8 gpm

## ACCESSORIES

PART NO.	DESCRIPTION
07641	Saw Chain, 15 in. / 38 cm Bar (.325 Pitch)
07935	File Guide with File, 21AP Chain (.325 in. Pitch)
07638	Saw Bar, 15 in. / 38 cm (.325 Pitch)
07629	Rim Sprocket, 7 Tooth (.325 Pitch)
11464	Scrench, (Combination Screwdriver-Bar Nut Wrench)

## WARRANTY

Stanley Hydraulic Tools and their associated parts are warranted against defects in materials and workmanship for a period of twelve months from the date of purchase. Stanley Hydraulic Tools reserves the right to repair or replace only those parts which prove to have been defective at the time of purchase. This warranty becomes void if maximum flow and pressure ratings are exceeded.