



## Long Reach Hydraulic Chainsaws

Super-Spool for use on Open and Closed Center Hydraulic Systems

Cuts hard-to-reach branches from the bucket or from the ground.

Available in three lengths, both standard and foam-filled

Insulated fibreglass tubes, available foam-filled for live-line tree trimming

Safety features include two-step trigger, trigger guard, and fully-covered sprocket guard.

Anti-kickback chain and chain oiler

Non-conductive hoses and bucket-mount tool holders are available to suit these saws.

Available with or without flush-face couplers

Rugged high-torque gear motor

### Models: Standard

**43178** - 62.5" (1.588m) overall length

**38568** - 75" (1.905m) overall length

**43177** - 88.5" (2.248m) overall length

### Models: Foam Filled

**LRF62/17141** - 62.5" (1.588m) overall length

**LRF75/17140** - 75" (1.905m) overall length

**LRF88/17142** - 88.5" (2.248m) overall length

## Specifications

**Weight:** See left

**Length:** See above

**Width:** 4" (102mm)

**Flow Range:** 5-8 GPM (19-30 L/MIN)

**Operating Pressure:** 1000-2000 PSI (69-140 BAR)

**Cutting Capacity:** 13" (330mm)

## Associated Products:

**Non-Conductive Hoses**

## Weight

### Models: Standard

**43178** - 8 1/2 lbs (3.9kg)

**38568** - 9 1/4 lbs (4.2kg)

**43177** - 9 3/4 lbs (4.4kg)

### Models: Foam Filled

**LRF62/17141** - 8 3/4 lbs (4.0kg)

**LRF75/17140** - 9 1/2 lbs (4.4kg)

**LRF88/17142** - 10 1/4 lbs (4.7kg)

**Phone 0800 48 2000**

**SALES • SERVICE • HIRE • CALIBRATION**