



Long Reach Hydraulic Chainsaws

Super-Spool for use on Open and Closed Center Hydraulic Systems

Cuts hard-to-reach branches from the bucket or from the ground.

Available in three lengths, both standard and foam-filled
Insulated fibreglass tubes, available foam-filled for live-line tree trimming

Safety features include two-step trigger, trigger guard, and fully-covered sprocket guard.

Anti-kickback chain and chain oiler

Non-conductive hoses and bucket-mount tool holders are available to suit these saws.

Available with or without flush-face couplers

Rugged high-torque gear motor

Models: Standard

43178 - 62.5" (1.588m) overall length

38568 - 75" (1.905m) overall length

43177 - 88.5" (2.248m) overall length

Models: Foam Filled

LRF62/17141 - 62.5" (1.588m) overall length

LRF75/17140 - 75" (1.905m) overall length

LRF88/17142 - 88.5" (2.248m) overall length

Specifications

Weight: See left

Length: See above

Width: 4" (102mm)

Flow Range: 5-8 GPM (19-30 L/MIN)

Operating Pressure: 1000-2000 PSI (69-140 BAR)

Cutting Capacity: 13" (330mm)

Associated Products:

Non-Conductive Hoses

Weight

Models: Standard

43178 - 8 1/2 lbs (3.9kg)

38568 - 9 1/4 lbs (4.2kg)

43177 - 9 3/4 lbs (4.4kg)

Models: Foam Filled

LRF62/17141 - 8 3/4 lbs (4.0kg)

LRF75/17140 - 9 1/2 lbs (4.4kg)

LRF88/17142 - 10 1/4 lbs (4.7kg)

Phone 0800 48 2000

SALES • SERVICE • HIRE • CALIBRATION