

# C023 UNDERWATER CUT-OFF SAW

# STANLEY®



The **C023** Cut-Off Saw is a hydraulic powered saw for dimensional cutting of metal, concrete, rock, masonry and coral. It has a high torque gear motor and 10" blade capacity for abrasive and diamond wheels with a 1" arbor. The **C023** is designed for underwater operation and is painted hi-visibility yellow.

## FEATURES

- Integral Stanley Hyrevz gear motor produces high torque
- Direct drive motor
- Stainless Steel spool and fasteners
- Adjustable shoe for precise cuts
- Interlocking safety trigger
- Cast aluminum handle and guard for durability
- Counter-clockwise rotation
- Wide flow range

## SPECIFICATIONS

<b>Capacity</b>	10" / 25.4 cm wheel
<b>Performance</b>	3275 rpm @ 15 gpm
<b>Arbor</b>	1" / 2½ cm
<b>Circuit Type</b>	Open Center
<b>Flow Range</b>	10-15 gpm / 38-57 lpm
<b>Optimum Flow</b>	15 gpm / 57 lpm
<b>Working Pressure</b>	1500-2000 psi / 105-140 bar
<b>Full Relief Setting</b>	2250 psi / 155 bar
<b>Weight</b>	23 lbs / 10.4 kg
<b>Length</b>	19½" / 49½ cm
<b>Width</b>	11" / 28 cm
<b>Hydraulic Ports</b>	-8 SAE O-ring
<b>Connection Size and Type</b>	½" Male Pipe Hose End
<b>Couplers</b>	No (See Accessories)
<b>Hose Whips</b>	Yes

# C023 UNDERWATER CUT-OFF SAW

# STANLEY®

## ORDERING INFORMATION

### PART NUMBER

**C023341** Cut-Off Saw, Underwater, 10" capacity with 1" arbor, less couplers

### ACCESSORIES

<b>03971</b>	Flush-Face Coupling Set, 3/8" NPT
<b>03974</b>	Flush-Face Coupling Set, 1/2" NPT
<b>06830</b>	Hose Whip 18" long, -8 SAE x 1/2" NPT
<b>03694</b>	10" / 25.4 cm diameter, 1" arbor, diamond blade for concrete
<b>04116</b>	10" / 25.4 cm diameter, 1" arbor, abrasive blade for concrete
<b>04117</b>	10" / 25.4 cm diameter, 1" arbor, abrasive blade for aluminum and metal
<b>31848</b>	Dual Hose, 50' x 1/2", with couplers
<b>31972</b>	Dual Hose, 25' x 1/2", with couplers
<b>58633</b>	Twinned Hose, 25' x 1/2", with couplers
<b>58634</b>	Twinned Hose, 50' x 1/2", with couplers

When hydraulic hose exceeds 100' (30.4 m) in length, increase I.D. of both pressure and return hose. For more information, consult Stanley Hydraulic Tools.

### IMPORTANT

To fill out a Product Warranty Recording form and for information on your warranty visit [stanleyhydraulic.com](http://stanleyhydraulic.com) and select the Warranty tab.



**Note:** The warranty recording form must be submitted to validate the warranty.

All Stanley Hydraulic Tools, parts, accessories and allied equipment are subject to design improvements, specifications and price changes at any time without notice and with no obligation to units already sold. Weights, dimensions and operating specifications listed herein are subject to change without notice. Where specifications are critical to your applications, please consult Stanley Hydraulic Tools.