


THE *PET & PAT-SERIES* TORQUE WRENCH POWER UNITS ARE PERFECTLY DESIGNED FOR OPERATING THE TW AND LPC -SERIES HYDRAULIC TORQUE WRENCHES.

They have a three stage pump for faster operation under load and incorporate a hydraulic oil cooler providing cool operation under continuous use. A 6 metre remote hand pendant is standard and one or two tools can be operated at one time due to the multi outlet pump block.



PET-1114

- ROLL CAGE**
for portability and protection
- LIQUID FILLED PRESSURE GAUGE**
has 1% accuracy and can be recalibrated. Scale is mpa/psi
- ELECTRIC MOTOR**
1.1 kW/240 Volt 50Hz induction motor 7.2 amp
- OIL COOLER**
electric fan operated for continuous duty operation
- 3 STAGE PUMP**
for increased speed under load
- MULTIPLE TOOL OUTLETS**
for operating one or two tools simultaneously
- ADJUSTABLE TORQUE CONTROL**
for accurate torque settings
- 6M REMOTE PENDANT**
through a 24 Volt transformer for safety. Incorporates motor ON/OFF button and ADV/AUTO RETRACT button



Model No.	Pressure Rating (bar)	Motor	Flow (Lpm)			Oil Capacity (L)	Dry Weight (kg)
			1st Stage 0-70 bar	2nd Stage 70-300 bar	3rd Stage 300-700 bar		
PET-1114	700	240 Volt / 50Hz	8	1.8	0.8	7.4	31
PAT-1114	700	1.1 kW Air	7	1.6	0.8	7.4	27

LIQUID FILLED PRESSURE GAUGE

has 1% accuracy and can be recalibrated. Scale is mpa/psi

AIR MOTOR

1.1 kW Ingersoll Rand®


ADJUSTABLE TORQUE CONTROL

for accurate torque settings

MULTIPLE TOOL OUTLETS

for operating one or two tools simultaneously

PAT-1114



ROLL CAGE

for portability and protection

6M REMOTE PENDANT

incorporates motor ON/OFF button and ADV/AUTO RETRACT button

OIL COOLER

keeps oil cool during heavy duty operation

3 STAGE PUMP

for increased speed under load

AIR FILTER/LUBRICATOR

for efficient operation



POWER REQUIREMENT

Electric 240 Volt 50 Hz
Air 1,400 Lpm @ 6.2 bar

FLOW

3 stage

MAXIMUM OPERATING PRESSURE

700 bar

E

BOLTING SOLUTIONS

Torque Wrench Hoses

Model No.	Length (m)	Description
TWH-04	4	Twin hose set to suit torque wrenches complete with male and female screw couplers at both ends. 700 bar working pressure. 2,800 bar min. burst.
TWH-06	6	
TWH-10	10	
TWH-15	15	



Did you know...

The **PET & PAT** hydraulic torque wrench power units are supplied with an oil cooler to allow continuous operation of hydraulic torque wrenches.

1



Torque Wrench Couplings

Model No.	Thread	Description	Suits Tool Model No.
CH-2	1/8" NPT MALE	Male half screw coupling complete with metal dust cap*	TW07, TW1 , LPC2
CR-2	1/8" NPT MALE	Female half screw coupling complete with metal dust cap*	TW07, TW1 , LPC2
CS-2	1/8" NPT MALE	Coupling set with metal dust caps* includes CH-2 and CR-2	TW07, TW1 , LPC2
CH-4	1/4" NPT FEMALE	Male half screw coupling complete with metal dust cap*	TW3 THROUGH TW50 LPC4 THROUGH LPC30
CR-4	1/4" NPT MALE	Female half screw coupling complete with metal dust cap*	TW3 THROUGH TW50 LPC4 THROUGH LPC30
CS-4		Coupling set with metal dust caps* includes CH-4 and CR-4	TW3 THROUGH TW50 LPC4 THROUGH LPC30



CH-2



CH-4



CR-2



CR-4



CS-2



CS-4

Snap couplings available. Consult Durapac for further information.

* Dust cap/s not shown