

## DURAPAC **HYDRAULIC COUPLINGS**

OFFER THE USER VARIOUS OPTIONS FOR EASY ASSEMBLY AND CONNECTION OF HYDRAULIC SYSTEMS AND TOOLS.

The CR-6 female high flow screw coupling with dust cap is standard supply on all Durapac cylinders. Other options available include 1/8" and 1/4" screw style couplings and snap together style where no oil spill on connection or disconnection is desirable. The GCS-210 is a gauge coupling set and is ideal for use when the pressure gauge needs to be removed from a system for protection and transportation.

### CH-2

1/8" male coupling with dust cap\* (1/8" NPT male)



### CR-2

1/8" female coupling with dust cap\* (1/8" NPT male)



### CS-2

Coupling set with dust caps\* includes CH-2 and CR-2



### CH-4

1/4" male coupling with dust cap\* (1/4" NPT female)



### CR-4

1/4" female coupling with dust cap\* (1/4" NPT male)



### CS-4

Coupling set with dust caps\* includes CH-4 and CR-4



### CH-6

3/8" male coupling with dust cap\* (3/8" NPT female)



### CR-6

3/8" female coupling with dust cap\* (3/8" NPT male)



### CS-6

3/8" coupling set with dust caps\* includes CH-6 and CR-6



### UDC-1

Universal dust cap to suit 3/8" male and female couplings



### CFH-6

Male half snap coupling with dust cap (3/8" NPT female)



### CFR-6

Female half snap coupling with dust cap (3/8" NPT female)



### CFS-6

Snap coupling set with dust caps includes CFH-6 and CFR-6



### GCS-210

Gauge coupling set with dust caps. Compact pin design



#### THREAD SIZES

**1/4", 1/8" & 3/8" NPT**  
**1/4" & 3/8" BSPP**

#### MAXIMUM OPERATING PRESSURE

**700 bar**

\* Dust cap not shown