

**DURAPAC HYDRAULIC COUPLINGS OFFER THE USER VARIOUS OPTIONS FOR EASY ASSEMBLY AND CONNECTION OF HYDRAULIC SYSTEMS AND TOOLS.**

The CR-6 female high flow screw coupling with dust cap is standard supply on all Durapac cylinders. Other options available include 1/8" and 1/4" screw style couplings and snap together style where no oil spill on connection or disconnection is desirable. The GCS-210 is a gauge coupling set and is ideal for use when the pressure gauge needs to be removed from a system for protection and transportation.

**D**  
**SYSTEM ACCESSORIES**



THREAD SIZES  
**1/4", 1/8" & 3/8" NPT**  
**1/4" & 3/8" BSPP**

MAXIMUM OPERATING PRESSURE  
**700 bar**

**CH-2**

1/8" male coupling with dust cap\* (1/8" NPT male)

**CR-2**

1/8" female coupling with dust cap\* (1/8" NPT male)

**CS-2**

Coupling set with dust caps\* includes CH-2 and CR-2

**CH-4**

1/4" male coupling with dust cap\* (1/4" NPT female)

**CR-4**

1/4" female coupling with dust cap\* (1/4" NPT male)

**CS-4**

Coupling set with dust caps\* includes CH-4 and CR-4

**CH-6**

3/8" male coupling with dust cap\* (3/8" NPT female)

**CR-6**

3/8" female coupling with dust cap\* (3/8" NPT male)

**CS-6**

3/8" coupling set with dust caps includes CH-6 and CR-6

**UDC-1**

Universal dust cap to suit 3/8" male and female couplings

**CFH-6**

Male half snap coupling with dust cap (3/8" NPT female)

**CFR-6**

Female half snap coupling with dust cap (3/8" NPT female)

**CFS-6**

Snap coupling set with dust caps includes CFH-6 and CFR-6

**GCS-210**

Gauge coupling set with dust caps. Compact pin design

1/4" NPT male  
1/4" NPT female

\* Dust cap not shown