

MODEL No.  
**SH-10(A)P**  
**SH-10(B)P**

Up to 104 mm diameter hole perforation on 3.2 mm thickness mild steel



## SPECIFICATIONS

Punching capacity  
 Stainless Steel :  
 1.6 mm plate thickness  
 Mild steel :  
 3.2 mm plate thickness  
 Hole diameter :  
 up to 104 mm (4 inch) es  
 Ram Stroke : 25 mm  
 Oil volume required : 40 cc  
 Output force : 87 kN at 59 Mpa pressure

## SIZE

63 (Dia) x 125 (H) mm

## WEIGHT

1.9 kg

## ACCESSORIES

Milli size punch sets are available on request.  
 M15, 16, 25, 30, 35, 40, 45, 50, 55, 57, 67,  
 70, 80, 82, 87, 95, 100, 108, 110

SH-10 (B) P



SH-10(A)P shown with carrying case

## FEATURES

Selection Chart :

SH-10 (A) P	SH-10 (B) P
1 HP-180N Hand Pump	
2 Setting threads (3/8" & 3/4")	
3 Collar (Large, Medium, Small)	
4 Steel carrying case	
A19 (3/4")	B16 (1/2")
A25 (1")	B22 (3/4")
A31 (1 1/4")	B28 (1")
A39 (1 1/2")	B36 (1 1/4")
A51 (2")	B42 (1 1/2")
	B54 (2")

## REMARKS

Punching size

Punch	Hole size
A19 (3 / 4)	19.8 mm
A25 (1)	26.1 mm
A31 (1 1 / 4)	32.5 mm
A39 (1 1 / 2)	38.7 mm
A51 (2)	51.6 mm
A63 (2 1 / 2)*	64.4 mm
A75 (3)*	77.2 mm
B16 (1 / 2)	21.8 mm
B22 (3 / 4)	27.6 mm
B28 (1)	34.1 mm
B36 (1 1 / 4)	42.7 mm
B42 (1 1 / 2)	48.7 mm
B54 (2)	60.5 mm
B70 (2 1 / 2)*	76.1 mm
B82 (3)*	88.9 mm
B92 (3 1 / 2)*	102.8 mm
B104 (4)*	115.5 mm

(\* ) marks show optional punch set available

**Phone 0800 48 2000**

**SALES • SERVICE • HIRE • CALIBRATION**