BÖRKEY
Inventor of Roller Skates

ROLLER SKATE - THE ROBUST - COMPLETE TRANSPORT KIT

MOD. HERCULES



Range of application:

- With the Hercules you do not have to waste time in assembling the unit, and the low level contributes to safer working conditions.
- The Hercules makes it easier and safer to move heavy loads. 24 and 30 mm diameter rollers in the chain are available. This turntable is larger than the one in the Transport Kit N.
- For larger loads we recommend the use of a second twin Skate Roller with turntable in the front, and two normal skates as stabilisers at the back.

MOD.	ROLLERS Ø Z	ROLLERS Ø E	LENGTH SUPPORT	WIDTH SUPPORT	TOTAL HEIGHT	SWIVEL-PL. Ø	MAX. LOAD kN	WEIGHT OF SET KG
HERKULES	30	24	200	130	110	250	350	68

BAUREIHE N

Range of application:

- For short, variable transportation distances.
- Movement of moderately heavy loads, e. g. machines, parts of machines and for installation works.
- A speed of 5 m/min should not be exceeded.
- It is possible to turn corners by placing turntables on top of the Roller Skates.
- Handles have to be attached but only guide the load while the Roller Skates are moving.
- Minimum turning circle is 3 m.

MOD.	ROLLERS Ø Z	LENGTH SUPPORT	WIDTH SUPPORT	TOTAL HEIGHT	SWIVEL-PL. Ø	MAX. LOAD kN	WEIGHT OF SET KG
I	18	120	120	108	130	200	48
II	24	120	120	117	130	300	56
III	30	130	130	140	150	600	90

BÖRKEY
Inventor of Roller Skates

ROLLER SKATE - THE ROBUST - COMPLETE TRANSPORT KIT

ACCESORY ONLY FOR MODELS ... N

TURNTABLE

MOD.	A	B	C	Ø D	E	F	G	I	WEIGHT KG
I	220	73	42	130	11	8	87	5	4,5
II	220	86	42	130	11	8	87	5	4,5
III	250	96	48	150	11	8	108	5	6,7
IV	275	114	61	190		3	165	11	13,7
V	360	128	61	220		3	235	11	18,9

PACKING PLATE / LEVELLING PLATE

MOD.	A	B	C	D	F	G	I	WEIGHT KG
I	149	73	42	120	8	87	5	3,7
II	149	86	42	120	8	87	5	3,7
III	178	96	48	130	8	108	5	5,3
IV	270	114	61	180	3	165	11	13,8
V	350	128	61	200	3	235	11	18,8