


Industrial Torque Wrench Adjustable Models


- Robust construction gives accurate results, to $\pm 4\%$, even in arduous working conditions.
- Every wrench supplied with a calibration certificate to satisfy requirements of ISO 9000:2000.
- The large break angle improves accuracy by reducing the possibility of over torquing.
- Cam control of the mechanism gives a controlled break which will not throw the operator off balance.
- Dual scaled, N.m and lbf.ft.
- Models 4R and 4AR are supplied in a carry case for storage and protection.
- If storage space is limited, for example in vehicle tool kits, models 4R to 5R can be supplied in two piece form where the longer of the pieces is 900mm.



Carry case standard with models 4R and 4AR



Adjusting Scale



Ratchet Adjustables

Model	Square Drive in*	Part Code	Range		Ratchet Diameter mm	Engagements per revolution	Length	Weight
			N.m	lbf.ft			mm	Kg
3AR	3/8	12001	100 – 500	70 – 350	70	48	915	5.2
4R	3/8	12006	150 – 700	100 – 500	70	48	1090	6.3
4AR	3/8	12007	200 – 800	150 – 600	70	48	1140	6.4
5R	3/8	12009	300 – 1000	200 – 750	70	48	1470	7.3
5AR	3/8	12012	700 – 1500	500 – 1000	70	48	1470	10.4

* 1" square drive versions are also available. Part Code becomes 12001.01 etc

Phone 0800 48 2000

SALES • SERVICE • HIRE • CALIBRATION