



Professional Torque Wrench

Models 550 - 1500

- Accuracy of $\pm 3\%$ of reading.
- Traceable calibration certificate supplied.
- Non length dependent. Extension handle can be used to reduce operator effort (handle supplied as standard with Model 800, 1000 and 1500).
- Positive 'click' can be heard, seen and felt.
- Low weight - Model 1000 just 5.8kg.
- Long scale length in N.m and lbf.ft allows error free setting.
- Fine 60 tooth ratchet allows the wrench to be used in confined areas.
- Supplied in carry case for storage and protection.



Extension Handle Part Code 14142 - supplied as standard with Models 800 to 1500

Ratchet Adjustables

Model	Square Drive	Part Code	Range		Ratchet Diameter	Engagements per revolution	Length	Length inc ext handle	Weight*
	in		N.m	lbf.ft	mm		mm	mm	Kg
550	3/8	14001	110 - 550	80 - 400	61	60	845	-	4.0
800	3/8	14015	200 - 800	150 - 600	75	60	1035	1535	5.2
800	1	14016	200 - 800	150 - 600	75	60	1035	1535	5.2
1000	3/8	14002	300 - 1000	220 - 750	75	60	1250	1750	5.8
1000	1	14003	300 - 1000	220 - 750	75	60	1250	1750	5.8
1500	3/8	14004	500 - 1500	370 - 1100	75	60	1570	2070	6.7
1500	1	14005	500 - 1500	370 - 1100	75	60	1570	2070	6.7

*Weight excluding extension handle. Extension handle, length 700 mm, weight 1.6 kg

Phone 0800 48 2000

SALES • SERVICE • HIRE • CALIBRATION