

## Utility Pruners



- Model 48200 has Super Sleeve™ for operation with Open- or Closed-Center hydraulic systems.
- Use on utility line clearing and selective pruning of shade trees.
- Heavy cut capacity cuts branches up to 2" (50 mm).
- Trigger guard.
- Insulated fiberglass extension tubes, tested to meet OSHA Regulation 1910.269.
- Heat-insulated handle.
- Full power return.

### SPECIFICATIONS

<b>Cutting Capacity</b>	2" (50 mm)
<b>System</b>	Super Sleeve™ for operation with Open- or Closed-Center hydraulic systems
<b>Extension Type</b>	Fiberglass – tested to 100 KvA for 5 minutes
<b>Weight</b>	
<b>48520 &amp; 48525</b>	0.7 lbs. (4.8 kg)
<b>48200</b>	12 lbs. (5.4 kg)
<b>Overall Length</b>	86" (2,159 mm)
<b>Width</b>	6-1/4" (158 mm)
<b>Flow Range</b>	4 - 6 gpm (15 - 23 lpm)
<b>Operating Pressure</b>	1,000 - 2,000 psi (69 - 140 bar)
<b>Pressure Port Thd.</b>	9/16 - 18 SAE O-Ring
<b>Return Port Thd.</b>	3/4 - 16 SAE O-Ring

	CAT. NO.	UPC NO.	DESCRIPTION
€	48200	48200	Utility Pruner, Super Sleeve™ operation for Open- or Closed-Center systems
€	48520	48520	Utility Pruner, Open-Center
€	48525	48525	Utility Pruner, Closed-Center
	54923	54923	HTMA Male Coupler
	54924	54924	HTMA Female Coupler

**Phone 0800 48 2000**

**SALES • SERVICE • HIRE • CALIBRATION**