



HIGH-PRESSURE PLUGS – PLUGY HP 6 BAR, 12 BAR AND 30 BAR

1. 14.

TYPE 26 (6 bar, 12 bar)



Savatech PLUGY HP plugs are specially reinforced plugs suitable for sealing of pipes with extremely high back pressures.

Special reinforcement

High back pressures

Heavy duty

PLUGY HP 30 BAR DESIGN

PLUGY HP 6 BAR
350 -500
60909



PLUGY HP 6 BAR, 12 BAR DESIGN



PLUGSY HP 30 BAR
537323



Front view

ACCESSORIES 6 BAR AND 12 BAR



SINGLE FITTING
CONTROLLER, 0.9 KG
12 BAR 531544
6 BAR 531542



INFLATION HOSE,
10 M, RED, 1.2 KG
74268



INFLATION HOSE,
10 M, BLUE, 1.2 KG
71248



INFLATION HOSE,
10 M, YELLOW, 1.2 KG
76686



POLY LIFT INFLATION
HOSE, 5 M, 1.9 KG
60957




POLY LIFT INFLATION
HOSE, 10 M, 2.4 KG
60958



ACCESSORIES 30 BAR



SINGLE FITTING
CONTROLLER, 0.9 KG
30 BAR
282184



INFLATION HOSE,
10 M, 4 KG
546714

PLUGY HP 6 BAR - BLOCKING PLUGS

PART NUMBER	NOMINAL SIZE	SIZE USAGE RANGE		REQUIRED INFLATION PRESSURE (BAR)	MAX. ALLOWED BACK PRESSURE (BAR)	DEFLATED PLUG		PRODUCT WEIGHT (KG)	Eye Bolt	Inflation Valve
		MIN. DIA. (MM)	MAX. DIA. (MM)			M Thread	Thread Size			
60887	100-150	100	150	6	3	92	535	1.2	6	R 1/4"
60907	150-200	150	200	6	3	142	575	2	8	R 1/4"
60908	200-300	200	300	6	3	192	635	3.2	8	R 1/4"
60909	350-500	350	500	6	3	322	865	8.7	8	R 1/4"
60924	500-600	500	600	6	3	472	1185	18	10	R 1/4"

PLUGY HP 12 BAR - BLOCKING PLUGS

PART NUMBER	NOMINAL SIZE	SIZE USAGE RANGE		REQUIRED INFLATION PRESSURE (BAR)	MAX. ALLOWED BACK PRESSURE (BAR)	DEFLATED PLUG		PRODUCT WEIGHT (KG)	Eye Bolt	Inflation Valve
		MIN. DIA. (MM)	MAX. DIA. (MM)			M Thread	Thread Size			
518561	100-125	100	125	12	10	92	540	1.5	6	R 1/4"
518562	150	150	150	12	10	142	580	2.7	8	R 1/4"
518563	200-250	200	250	12	10	192	640	4.3	8	R 1/4"
518564	300-350	300	350	12	10	272	670	8	8	R 1/4"
518565	400	400	400	12	10	322	870	11.5	10	R 1/4"
518566	500	500	500	12	10	472	1190	24.1	10	R 1/4"

PLUGY HP 30 BAR - BLOCKING PLUGS

PART NUMBER	NOMINAL SIZE	SIZE USAGE RANGE		REQUIRED INFLATION PRESSURE (BAR)	MAX. ALLOWED BACK PRESSURE (BAR)	DEFLATED PLUG		RUBBER SLEEVE LENGTH (MM)	PRODUCT WEIGHT (KG)
		MIN. DIA. (MM)	MAX. DIA. (MM)			Diameter (mm)	Length (mm)		
538625	55-75	55	75	30	16	54	615	400	3
533837	75-100	75	100	30	16	73	600	400	5
533838	100-150	100	150	30	16	88	614	400	6.7
533839	150-200	150	200	30	16	122	621	400	13

PLUGSY HP 30 BAR - BYPASS PLUGS

PART NUMBER	NOMINAL SIZE	SIZE USAGE RANGE		REQUIRED INFLATION PRESSURE (BAR)	MAX. ALLOWED BACK PRESSURE (BAR)	Flow Through (mm)	Bypass Thread ["]	RUBBER SLEEVE LENGTH (MM)	PRODUCT WEIGHT (KG)
		MIN. DIA. (MM)	MAX. DIA. (MM)						
537553	55-75	55	75	30	16	10	3/8	400	3
537661	75-100	75	100	30	16	15	1/2	400	4.8
537323	100-150	100	150	30	16	20	3/4	400	7
537672	150-200	150	200	30	16	25	1	400	13