



Savatech multi-size pipe plugs PLUGY and PLUGSY are reinforced with aramid cord and are noted for a wide application range. Each plug covers several pipe sizes. Multi-size ranges overlap to meet specific requirements. They can cover pipe diameters from 40 mm to 1800 mm. Plugs are flexible and bend easily around tight corners or when inserted through the manholes.



Aramid reinforcement	Flexible construction	Suitable for EN 1610 tightness test	Oil-resistant version available
----------------------	-----------------------	-------------------------------------	---------------------------------

PLUGY 350-600
60422



PLUGSY 350-600
60440



PLUGY 600-1200
523941




PLUGSY 600-1200
523942




ACCESSORIES




SINGLE FITTING CONTROLLER,
0.9 KG
3.0 BAR 537048
2.5 BAR 60310
1.5 BAR 74609
1.0 BAR 74653




HAND HELD SINGLE DEADMAN 2.5 BAR,
0.9 KG
519442




INFLATION HOSE,
10 M, RED,
1.2 KG
74268




INFLATION HOSE,
10 M, BLUE,
1.2 KG
71248




INFLATION HOSE,
10 M, YELLOW,
1.2 KG
76686



POLY LIFT INFLATION HOSE,
5 M, 1.9 KG
60957
10 M, 2.4 KG
60958



REMOTE PLACEMENT FOR:
PLUGY 100-200
0.8 KG 503403
PLUGY 200-400
1 KG 503404
PLUGY 350-600,
500-1000
1.5 KG 503406



TELESCOPIC 3-PART ALU POLE
1 KG
529039

PLUGY - BLOCKING PLUGS

PART NUMBER	NOMINAL SIZE	SIZE USAGE RANGE		REQUIRED INFLATION PRESSURE (BAR)	DEFLATED PLUG		PRODUCT WEIGHT (KG)	EYE BOLT		INFLATION VALVE
		MIN. DIA. (MM)	MAX. DIA. (MM)		DIAMETER (MM)	RUBBER LENGTH (MM)		M THREAD	THREAD SIZE	
519423	40-70	40	70	2.5	35	160	0.2	NA	R 1/4"	
519424	70-150	70	150	2.5	68	300	0.4	NA	R 1/4"	
60417	100-200	100	200	2.5	92	500	1.35	M6	R 1/4"	
526850	150-200	150	200	2.5	142	350	1.85	M8	R 1/4"	
60418	150-300	150	300	2.5	142	540	2.6	M8	R 1/4"	
60419	200-400	200	400	2.5	192	600	3.6	M8	R 1/4"	
60599	300-525	300	525	2.5	272	630	6.8	M8	R 1/4"	
60422	350-600	350	600	2.5	322	830	9.8	M10	R 1/4"	
60606	375-750	375	750	2.5	342	1050	11.9	M10	R 1/4"	
60453	500-800	500	800	2.5	472	1150	19.5	M10	R 1/4"	
60425	500-1000	500	1000	1.5	472	1150	19.5	M10	R 1/4"	
523941	600-1200	600	1200	1.5	574	1450	38	M10	2 x R 3/8"	
78959	750-1500	750	1500	1	600	2300	75	M10	2 x R 1/4"	
535881	800-1800	800	1800	1	600	3000	106	M10	2 x R 1/4"	

PLUGSY - BYPASS PLUGS

PART NUMBER	NOMINAL SIZE	SIZE USAGE RANGE		REQUIRED INFLATION PRESSURE (BAR)	DEFLATED PLUG		PRODUCT WEIGHT (KG)	EYE BOLT		INFLATION VALVE	BYPASS DIAMETER (FEMALE)
		MIN. DIA. (MM)	MAX. DIA. (MM)		DIAMETER (MM)	RUBBER LENGTH (MM)		M THREAD	THREAD SIZE		
526849	70-150	70	150	2.5	68	300	1.7	NA	R 1/4"	1/2"	
60429	100-200	100	200	2.5	92	500	2.7	M6	R 1/4"	1"	
526851	150-200	150	200	2.5	142	350	3.3	M8	R 1/4"	1"	
60432	150-300	150	300	2.5	142	540	4.3	M8	R 1/4"	1"	
60434	200-400	200	400	2.5	192	600	7	M8	R 1/4"	2"	
60630	300-525	300	525	2.5	272	630	12	M8	R 1/4"	2"	
60440	350-600	350	600	2.5	322	830	16	M10	R 1/4"	2"	
60632	375-750	375	750	2.5	342	1050	19.7	M10	R 1/4"	2"	
60454	500-800	500	800	2.5	472	1150	32.5	M10	R 1/4"	2"	
60442	500-1000	500	1000	1.5	472	1150	32.5	M10	R 1/4"	2"	
523942	600-1200	600	1200	1.5	574	1450	55.5	M10	2 x R 3/8"	4"	
78960	750-1500	750	1500	1	600	2300	91	M10	2 x R 1/2"	4"	
535882	800-1800	800	1800	1	600	3000	117	M10	2 x R 1/2"	4"	

BACK PRESSURES (bar)* - PLUGY, PLUGSY

PLUG SIZE	PIPE DIAMETER (MM)																				
	40	70	100	150	200	250	300	350	400	500	600	800	1000	1200	1300	1400	1500	1600	1700	1800	
40-70	2	1.2																			
70-150		2.2	1.7	1.3																	
100-200			2.2	1.7	1.3																
150-200				2	1.5																
150-300				2.2	2	1.4	1.2														
200-400					2.2	2	1.7	1.5	1.2												
300-525							2	1.7	1.5	1.2											
350-600								2.1	1.9	1.6	1.3										
375-750									2	1.7	1.4										
500-800										1.8	1.4	1.1									
500-1000										1	0.8	0.6	0.5								
600-1200											1	0.7	0.6	0.5							
750-1500												1	0.9	0.8	0.7	0.6	0.5				
800-1800													1	1	0.9	0.8	0.7	0.6	0.5	0.5	0.4

* measured in a dry iron pipe