

RATCHET JACKS

- 8 Models.
- Double-lever sockets for jacking in close quarters.
- Multiple-tooth pawls for strength & safety.
- Drop-forged, alloy steel, heat-treated components.
- Adjustable spring links.
- Plated springs to resist corrosion.
- Precision machining throughout.
- Large base insures a firm foundation.
- Supports full rated capacity on the toe or the cap.



Model 85A is used to lift a CNC machine for installation. 5 ton lifting capacity, low toe height and light weight make the models 84A, 85A, & 86A universal tools. 10 ton models 1017 & A1022 are used extensively by structural movers, riggers & maintenance crews.

- **5 Ton Ratchet Jacks**^d
These units are all mechanically identical and vary only in stroke and height.

- **10 Ton Ratchet Jacks**
The 1017 and 22B incorporate a ductile iron housing for maximum durability. The A1022, which is identical to the 22B except for an aluminum housing, is the ideal choice when portability is important. These jacks are often selected for lifts of 10 tons or less because of their low handle effort.

MECHANICAL JACKS



- **A1538 Utility Pole Jack**
Light weight aluminum alloy housing is used for pole lining maintenance by telephone, light and power, and railroad companies. Jack pivots, I-Beam base assures firm foundation. Alloy steel chain, I-Beam base, and steel lever bar are all ordered separately.

I Beam Base Order#: 10600
Alloy Chain Order#: 10760

Ratchet Jacks

Model Number	Supporting Cap. (tons)	Lifting Cap. (tons)	Stroke (mm)	Handle Effort per Ton (kg)	Cap. Min. Height (mm)	Toe Min. Height (mm)	Base Size (mm)	Weight (kg)	Steel Lever Bars				
									Order Number	Length (mm)	Dia. (mm)	Weight (kg)	
84A	5	5	178	14,5	356	44	127 x 187	12,7	10640	914	25	3,7	
85A			254		432								13,6
86A			330		508								15,9
1017	10	10	241	13,6	438	57	152 x 222	18,2	10665	1524	32	7,7	
A1022			305		21,8								19,1
22B			305		21,8								31,8
A1538	15	8	559	14,5	----	----	203 x 210	28,2	10675	1829	32	9,1	
24A	20	15	330	14,5	591	57	203 x 260	42,3					
2029			457	718	203 x 279	47,3							

Pivot Bases are included on model A1538.
Optional for the A1538 are I-Beam Base (#10600) and Chain (#10760).

Note: 10665 & 10675 lever bars are interchangeable. The longer 10675 bar results in lower handle efforts.

Phone 0800 48 2000

SALES • SERVICE • HIRE • CALIBRATION