



Grinders

GR29 U/W

SPECIFICATIONS

ITEM	U.S.A.	METRIC
CAPACITY	9 in. Wheel on 5/8 in.-11 Arbor	
RPM	2700 @ 10 gpm	2700 @ 38 lpm
WEIGHT (with guard)	14 lb	6.4 kg
LENGTH	11 in.	28 cm
WIDTH (with guard)	12 in.	30.5 cm
PRESSURE	1000-2500 psi	70-176 bar
FLOW RANGE	4-10 gpm	15-38 lpm
OPTIMUM FLOW	10 gpm	38 lpm
PORTING	-8 SAE O-ring	
HOSE WHIPS	No	
MOTOR	Stanley Hyrevz™ Gear	

Features and Benefits

Stanley's Underwater GR29 Grinder can be used for grinding and cleaning with either cup or standard grinding wheels, wire or nylon brushes.

The integral Stanley Hyrevz™ gear motor is manufactured to exacting standards to deliver maximum efficiency.

The plastisol covering the handle transmits very little heat. The plastisol gives a more comfortable grip to the tool.

There are two positions available for the assist handle to be conveniently placed by the operator. Either position is at a most comfortable handling position from the valve handle.

The wheel guard is adjustable. By loosening the clamp screw the guard may be rotated to any convenient position.

Phone 0800 48 2000

SALES • SERVICE • HIRE • CALIBRATION



"Makin' the Hard Jobs Easy"

ORDERING INFORMATION

MODEL	DESCRIPTION
GR29310	Grinder, Underwater, less couplers
GR2930101	Grinder, Underwater, couplers, CE

CE = Designed to Meet Requirements of European Communities

WARRANTY

Stanley Hydraulic Tools and their associated parts are warranted against defects in materials and workmanship for a period of twelve months from the date of purchase. Stanley Hydraulic Tools reserves the right to repair or replace only those parts which prove to have been defective at the time of purchase. This warranty becomes void if maximum flow and pressure ratings are exceeded.

ACCESSORIES

PART NO.	DESCRIPTION
02587	Grinding wheel for Metal, 9-inch diameter x 5/8-11 thread
02588	Grinding wheel for Masonry, 9-inch diameter x 5/8-11 thread
03691	Grinding wheel, 7-inch diameter x 5/8-11 thread
05194	Adapter, 5/8-11 thread, depressed center wheel

Phone 0800 48 2000

SALES • SERVICE • HIRE • CALIBRATION