

## Model IW12



Stanley's hydraulic impact wrenches are used around the world by electric and gas utilities, construction crews, municipal agencies, and railroad crews.

No other tool, whether air or electric driven, can match the power, light weight and overall efficiency of our impact wrenches.

The IW12 can handle a wide variety of applications. The IW12 impact wrench features adjustable impact intensity.

The rugged impact wrench mechanism is simple to maintain and has many features to give it proven reliability. Torque transmission to the operator is minimal with the swing hammer design.

Designed to run from a wide range of hydraulic circuits, the IW12 is used for nut, bolt and anchor bolt driving and is equally popular for wood boring and drilling.

The larger feathering trigger is convenient to use and gives the operator complete control of the wrench. The standard reversing valve provides instant reverse.

For operator comfort the IW12 handle is coated with a heat insulating, shock absorbing material.

**Underwater models available.**

### SPECIFICATIONS

ITEM	U.S.A	METRIC
Chuck Type - Sq Drive	3/4"	1.9cm
Weight	14lb	6.4 kg
Length	9.5"	24.1 cm
Width	4"	10.2cm
Hydraulic Pressure	1000-2000psi	70-140 bar
Torque	250-1200 ft lb	340-1632 Nm
Flow Range	4-12 gpm	15-45 lpm
Optimum Flow	5-10 gpm	20-38 lpm
Porting	-8 SAE O-ring	
Connect Size & Type	3/8" Male Pipe Adapter	
Motor	Integral	

**Phone 0800 48 2000**

**SALES • SERVICE • HIRE • CALIBRATION**